

Thumb Shifters MTB

| Model No. | SLM96 | | | | |
|-----------------------|--------------------------|---------------|----------------|--------------------------|---------------------|
| | R9 | R8 | RF | L3 | LF |
| Side and Speed | Right 9-Speed | Right 8-Speed | Right Friction | Left 3-Speed | Left Friction (3/2) |
| Lever Position Adjust | • | • | • | • | • |
| Lever Material | Aluminum / High-Polished | | | Aluminum / High-Polished | |
| Clamp Material | Aluminum | | | Aluminum | |
| Cable Adjuster | X | | | X | |
| Cable Type | Slick-Galvanized | | | Slick-Galvanized | |
| Cable Length | 1,950mm | | | 1,450mm | |
| Casing Compatibility | SP & ↑ | | | SP & ↑ | 2SP & ↑ |
| Handle Bar Diameter | 22.2mm* | | | 22.2mm* | |
| Average Weight | 87g | 87g | 87g | 85g | 85g |

* Tighten Torque of 60~ 80 kgf-cm

Thumb Shifters MTB

| Model No. | SLM2T | | | | SLM10 | |
|----------------------|----------------------|---------------|---------------|----------------------|------------------------|---------------------|
| | R7 | R6 | R5 | LF | RF | LF |
| Side and Speed | Right 7-Speed | Right 6-Speed | Right 5-Speed | Left Friction (3/2) | Right Friction (7/6/5) | Left Friction (3/2) |
| Lever Material | Engineering Polymers | | | Engineering Polymers | Aluminum | Aluminum |
| Clamp Material | Steel | | | Steel | Steel | Steel |
| Cable Adjuster | X | | | • | X | |
| Cable Type | Galvanized | | | Galvanized | Galvanized | |
| Cable Length | 1,900mm | | | 1,450mm | 1,950mm | 1,450mm |
| Casing Compatibility | 2SP & ↑ | | | 2SP & ↑ | 2SP & ↑ | |
| Handle Bar Diameter | 22.2mm* | | | 22.2mm* | 22.2mm* | |
| Average Weight | 64.5g | 64.5g | 64.5g | 65g | 64.5g | 61.5g |

* Tighten Torque of 20~ 25 kgf-cm